



Laykold®

Masters Line Prime

Features and Benefits

1. General Description

Laykold Masters Line Prime is a 100% acrylic, clear drying, emulsion primer that is applied prior to Laykold Masters White Line Paint. The use of the Laykold Masters Line prime assures crisp, sharp lines and a professional quality finish to the court surface.

Laykold Masters Line Prime is environmentally friendly containing no asbestos, Lead, or Mercury.

Basic Use: Laykold Masters Line Prime is designed to fill the minor voids between the tape and court surface.

2. Safety Guidelines

Always wear the recommended personal protective equipment. Avoid contact with eyes, skin, and clothing.

3. Storage and Packaging

Laykold Masters Line Prime should be kept dry and cool. Storage temperature should be between 10°C (50°F) and 38°C (100°F). Do not store in direct sunlight.

Packaging: 2 gallon unit (2 gallon units are packaged in jugs at 1 gallon each).

4. Coverage

Depending on the surface porosity and texture, the consumption rate is 500-600 feet of 2" line per gallon. One set of tennis court lines typically requires 1 gallon of Laykold Masters Line Prime.

5. Installation Guidelines

Apply Laykold Master Line Prime undiluted with a paint brush or roller after masking tape is put down. Laykold Masters Line Prime dries within 10 to 15 minutes in good weather conditions. Do not apply masking tape and Laykold Masters Line Prime if rain is imminent. Once Laykold Masters Line Prime is dry, Laykold Masters White Line Paint may be applied. Remove masking tape immediately after playing lines are dry.

- ✓ Crisp, sharp lines
- ✓ Professional quality finish
- ✓ Environmentally friendly
- ✓ Contains no asbestos, Lead, or Mercury
- ✓ One component



6. Limitations

- Minimum surface and application temperature: 10°C (50°F)
- Maximum surface and application temperature: 54°C (130°F)
- Do not allow when rain is imminent
- Do not allow to freeze
- Do not dilute
- Completed projects should be allowed a minimum of 48 hours of drying time before releasing for play. CAUTION: acrylic coatings can take 2 to 4 weeks to fully cure depending on weather conditions.

7. Technical Data

Results based on temperature of 23°C (73°F) and 50% Humidity

Flammability	Non-Flammable
Flash Point	None
Color	Milky White, clear when dry

*Based on standard formula calculation

Above figures are guide values and should not be used as a base for specifications

Consult the Safety Data Sheet (SDS) for more details

For complete and latest warranty and product information, please visit www.advpolytech.com

