



Advanced Polymer Technology
APT Worldwide - Always 'APT'



Laykold®

White Line Paint

1. General Description

Laykold White Line Paint is a water-based, 100% acrylic emulsion line marking paint. Formulated without solvents or oils that tend to attack the underlying surface.

Laykold White Line Paint is also environmentally friendly containing no asbestos, Lead, or Mercury.

Basic Uses: Laykold White Line Paint is used for marking lines over color coating materials on tennis courts, basketball courts, and other recreational surfaces.

2. Safety Guidelines

Always wear the recommended personal protective equipment. Avoid contact with eyes, skin, and clothing.

3. Storage and Packaging

Laykold White Line Paint should be kept dry and cool. Storage temperature should be between 4°C (40°F) and 32°C (90°F).

Packaging: 5 gallon unit or 2 gallon unit (2 gallon units are packaged in jugs at 1 gallon each).

4. Coverage

Laykold White Line Paint coverage is approximately 0.75-1 gallon(s) (3.9 – 5.2 kgs) of line paint per standard size tennis court.

5. Installation Guidelines

Wait approximately 24 hours, after applying color coatings, before applying White Line Paint. For indoor installations, wait until color coating materials are thoroughly cured.

Mix Laykold White Line Paint completely before applying. Do NOT add water. Tape and measured lines should be in accordance with the United States Tennis and Track Builders Association specifications.

Features and Benefits

- ✓ Environmentally friendly
- ✓ Water based
- ✓ Contains no solvents or oils
- ✓ Contains no asbestos, Lead, or Mercury
- ✓ Good hiding properties



White Line Paint

Using a high quality roller, roll line paint for 1-2 coats, as specified. To improve crispness of the finished line, prime the tape, prior to application of the line paint, with the same finish color coat material in which the surface has been coated.

6. Limitations

- Do not apply when surface temperature exceeds 130° (54°C).
- Do not apply when temperatures are below 50°F (10°C) or when rain is imminent.
- Do not allow to freeze.
- Do not dilute.
- Drying time of 2-4 hours depending on weather conditions.

7. Technical Data

Results based on temperature of 77°F and 50% humidity

VOC		29.5 g/L*
Viscosity		25,000 – 35,000 cPs

**based on standard formula calculation*

Above figures are guide values and should not be used as a base for specifications

Consult the Material Safety Data Sheet / Safety Data Sheet for more details.

For complete and latest warranty and product information, please visit www.advpolytech.com



ADVANCED POLYMER TECHNOLOGY CORPORATION believes the information herein to be true, accurate and reliable. However, recommendations or suggestions are made without guarantee. Since conditions and disposal are beyond our control, ADVANCED POLYMER TECHNOLOGY CORPORATION disclaims any liability incurred in connection with the use of our products and information contained herein; no warranty, express or implied is given nor is freedom from any patent owned by ADVANCED POLYMER TECHNOLOGY CORPORATION or others to be inferred.

Revision Date: 11/08/12