



Advanced Polymer Technology

APT Worldwide - Always 'APT'



Laykold® Line Prime

1. General Description

Laykold Line Prime is a 100% acrylic clear drying emulsion primer that is applied prior to Laykold White Line Paint. The use of Laykold Line Prime assures crisp, sharp lines and a professional quality finish to the court surface.

Laykold Line Prime does not contain any asbestos, Lead, or Mercury.

Basic Uses: Designed to fill the minor voids between the tape and the court surface.

2. Safety Guidelines

Always wear the recommended personal protective equipment. Avoid contact with eyes, skin, and clothing.

3. Storage and Packaging

Line Prime should be kept dry and cool. Storage temperature should be between 10°C (50°F) and 38°C (100°F). Do not store in direct sunlight.

Packaging: 2 gallon unit (2 gallon units are packaged in jugs at 1 gallon each).

4. Coverage

Depending on the surface porosity and texture the consumption rate is 500 - 600 feet of 2" line per gallon. One set of tennis court lines typically requires 1-gallon of Laykold Line Prime.

5. Installation Guidelines

Apply Laykold Line Prime undiluted with a paintbrush or roller after masking tape is put down. Laykold Line Prime dries within 10 to 15 minutes in good weather conditions. Do not apply masking tape and Laykold Line Prime if rain is imminent. Once Laykold Line Prime is dry, Laykold White Line Paint may be applied. Remove masking tape immediately after playing lines are dry.

6. Limitations

- Minimum surface and application temperature: 10°C (50°F)
- Maximum surface and application temperature : 54°C (130°F)
- Do not allow product to freeze.

Features and Benefits

- ✓ Crisp, Sharp lines
- ✓ Professional quality finish
- ✓ Environmentally friendly
- ✓ Does not contain any asbestos, Lead, or Mercury
- ✓ One component



Line Prime

- Do not dilute with water.
- Do not apply when rain is imminent.
- Completed projects should be allowed a minimum for 48 hours drying time before releasing for play.
CAUTION: acrylic coatings can take 2 to 4 weeks to fully cure depending on weather conditions.

7. Technical Data

Results based on temperature of 77°F and 50% Humidity

Flammability		Non-Flammable
Flash Point		None
Color		Milky White, clear when dry

Above figures are guide values and should not be used as base for specifications.

Consult the Safety Data Sheet (SDS) for more details.

For complete and latest warranty and product information, please visit www.advpolytech.com

